Amendments to the Claims

- 1. (previously presented) A solventless pressure sensitive adhesive (PSA) comprising (A) 15 to 40 weight percent of at least one organosiloxane polymer having on average at least two aliphatic unsaturations per molecule; (B) 50 to 80 weight percent of at least one resin having R₃SiO_{1/2} (M units) and SiO_{4/2} (Q units) where each R is an independently chosen monovalent hydrocarbon group free from aliphatic unsaturation and comprising 1 to 20 carbon atoms; (C) 2 to 7 weight percent of at least one reactive diluent; (D) at least one Si-H containing crosslinker comprising an organohydrogensilicon compound having on average at least two silicon bonded hydrogen atoms per molecule; (E) at least one hydrosilylation catalyst; and (F) optionally at least one inhibitor.
- 2. (Canceled)
- 3. (previously presented) The solventless PSA of claim 1 where Component (A) is chosen from hexenyldimethylsiloxy-terminated polydimethylsiloxane-polymethylhexenylsiloxane copolymers, hexenyldimethylsiloxy-terminated polydimethylsiloxane polymers, vinyl or hexenyldimethylsiloxy-terminated polydimethylsiloxane polymers, vinyl or hexenyldimethylsiloxy-terminated poly(dimethylsiloxane-silicate) copolymers, mixed trimethylsiloxy-vinyldimethylsiloxy terminated poly(dimethylsiloxane-vinylmethylsiloxane-silicate) copolymers, and vinyl or hexenyldimethylsiloxy terminated poly(dimethylsiloxane-hydrocarbyl) copolymers having a viscosity from 150 to 499 mPa.s at 25°C.
- 4. (currently amended) The solventless PSA of any of claims 1 or 3 where claim 1 where component (D) is chosen from
- (D1) diorganohydrogensiloxy-terminated polydiorganosiloxane polymers, diorganohydrogensiloxy-terminated polydiorganohydrogensiloxane polymers, diorganohydrogensiloxy-terminated polydiorganosiloxane-polyorganohydrogensiloxane copolymers, triorganosiloxy-terminated polydiorganosiloxane-polyorganohydrogensiloxane copolymers, triorganosiloxy-terminated polyorganohydrogensiloxane polymers where the organo

substituent on these organohydrogensiloxanes comprises a monovalent hydrocarbon group having from 1 to 20 carbon atoms;

(D2) an organohydrogensiloxane reaction product having a viscosity of from 150 to 50,000 mPa.s obtained by mixing: (a) at least one organohydrogensiloxane containing at least three silicon-bonded hydrogen groups per molecule, (b) at least one compound containing at least two alkenyl groups per molecule, and (c) a platinum group metal-containing catalyst which is present in an amount sufficient to provide 0.1 to 10 weight parts of platinum group metal per million weight parts of (a)+(b), with the proviso that the ratio of the number of silicon-bonded hydrogen atoms of Component (a) to the number of alkenyl groups of Component (b) is at least 4.6:1; and (D3) an organohydrogensiloxane containing at least two silicon-bonded hydrogen atoms per

molecule described by formula (II):

where each R is independently selected from a hydrogen atom and a monovalent hydrocarbon group comprising 1 to 20 carbon atoms which is free from aliphatic unsaturation, a is an integer from 1 to 18, b is an integer from 1 to 19, a + b is an integer from 3 to 20, each X is an independently selected functional group selected from a halogen atom, an ether group, an alkoxy group, an alkoxyether group, an acyl group, an epoxy group, an amino group, or a silyl group, or a –Z-R⁴ group, where each Z is independently selected from an oxygen and a divalent hydrocarbon group comprising 2 to 20 carbon atoms, each R⁴ group is independently selected from -BR_uY_{2-u}, -SiR_vY_{3-v}, or a group described by formula (III):

$$\begin{split} &(Y_{3-n}R_nSiO_{1/2})_c(Y_{2-o}R_oSiO_{2/2})_d(Y_{1-p}R_pSiO_{3/2})_e(SiO_{4/2})_f(CR_qY_{1-q})_g(CR_rY_{2-r})_h\\ &(O(CR_sY_{2-s})_i(CR_tY_{3-t})_j \end{split}$$

where B refers to boron, each R is as described above, the sum of c+d+e+f+g+h+i+j is at least 2, n is an integer from 0 to 3, o is an integer from 0 to 2, p is an integer from 0 to 1, q is an integer from 0 to 1, r is an integer from 0 to 2, s is an integer from 0 to 2, t is an integer from 0 to 3, u is Page 4 of 7

an integer from 0 to 2, v is an integer from 0 to 3, each Y is an independently selected functional group selected from a halogen atom, an ether group, an alkoxy group, an alkoxyether group, an acyl group, an epoxy group, an amino group, or a silyl group, or a Z-G group, where Z is as described above, each G is a cyclosiloxane described by formula (IV):

where R and X are as described above, k is an integer from 0 to 18, m is an integer from 0 to 18, k+m is an integer from 2 to 20, provided in formula (III) that one of the Y groups is replaced by the Z group bonding the R^4 group to the cyclosiloxane of formula (II), and provided further if g+h+i+j>0 then c+d+e+f>0.

- 5. (currently amended) The solventless PSA of any of claims 1, 3 or 4claim 1 where the reactive diluent comprises at least one hydrocarbon compound comprising 8 to 18 carbon atoms and at least one aliphatic unsaturation.
- 6. (currently amended) The solventless PSA any of claims 1 and 3 5 of claim 1 where the reactive diluent comprises at least one alkene comprising 12 to 14 carbon atoms having a terminal double bond.
- 7. (currently amended) The solventless PSA any of claims 1 and 3 6 of claim 1 where the reactive diluent is tetradecene.
- 8. (currently amended) The solventless PSA any of claims 1 and 3-7 of claim 1 where the M:Q ratio of the resin (B) is from 0.6:1 to 1.9:1 and it contains no more than 1 weight percent silanol.
- 9. (currently amended) An article having on at least one surface the solventless PSA of elaims 1 and 3 8 claim 1.

10. (original) The article of claim 9 where the article is chosen from polyester film, polyimide film, silicone rubber or foam, metal, glass impregnated cloth, paper or plastic coated paper, and fluorocarbon or fluorosilicone treated supports.